

REMARKS

The specification of the subject U.S. patent application, as filed, as constituted by the verified translation of PCT/EP2005/050261, has been cancelled in favor of the concurrently submitted Substitute Specification. A suitable Abstract of the Disclosure has been added. These changes and additions do not constitute any new matter.


Original claims 1-71, and Article 19 claims 1-56 have been cancelled. New claims 72-123 have been added. New claims 72-123 are essentially the same, in scope as the claims currently pending in the PCT application. They have been rewritten in a form more in accordance with U.S. practice and eliminating multiple dependencies.

Entry of this Preliminary Amendment into the file of the subject U.S. patent application, prior to the calculation of the filing fee, and prior to an examination of the application on the merits, is respectfully requested.

Respectfully submitted,

Günther Oskar ECKERT
Applicant

JONES, TULLAR & COOPER, P.C.
Attorneys for Applicants



Douglas R. Hanscom
Reg. No. 26,600

July 21, 2006
JONES, TULLAR & COOPER, P.C.
P.O. Box 2266 Eads Station
Arlington, Virginia 22202
(703) 415-1500
Attorney Docket: W1.2227 PCT-US

MARKED-UP COPY OF SPECIFICATION**ECKERT, W1.2227 PCT-US****[Specification]**

**PRINTING MACHINE WITH A DEVICE AND A METHOD FOR COMPENSATION OF A
LONGITUDINAL ELONGATION AND A TRANSVERSE ELONGATION OF A PRINTED
WEB PRINTED IN DIFFERING PRINTING COUPLES**

CROSS-REFERENCE TO RELATED APPLICATIONS

[001] This patent application is the U.S. national phase, under 35 USC 371, of
PCT/EP2005/050261, filed January 21, 2005; published as WO 2005/072966 A1 on
August 11, 2005 and claiming priority to DE 10 2004 004 263.2, filed January 28, 2004,
the disclosures of which are expressly incorporated herein by reference.

FIELD OF THE INVENTION

[002] The present invention is directed[relates] to printing presses with several
printing groups, which generate at least one printed image on a material to be imprinted,
and to methods for compensating for a longitudinal elongation and/or a transverse
elongation of a material to be imprinted[, in accordance with the preambles of claims 1, 3,
5, 7, 46, 48 or 65]. Each of the printing groups includes a forme cylinder and an ink
transfer cylinder which form a portion of the printed image. The elongation of the material

to be printed is a factor in the location of printing formes on the successive forme cylinders.

BACKGROUND OF THE INVENTION

[003] A method and a device for use in adapting the position of printing plates to a deformation of a paper web to be imprinted by [means of]printing rollers is known from DE 195 16 368 A1. The[, wherein the] printing plate, or the holder receiving it in a punching and/or bending machine, is respectively displaced or is offset in the lateral direction, in the circumferential direction and/or in its angular position by those amounts which the printing plate requires on its printing roller because of the deformation of the paper web. This is done[,] in order to provide an imprint which corresponds[corresponding] with a previous printing roller₁ in the feeding direction of the paper web₁ in spite of the deformation of the paper web which had taken place in the meantime. Bending[, and wherein bending] and/or punching of the plate or holder is performed on this printing plate displaced from its zero position. A[, for which purpose a] computer-controlled alignment device₁ in the punching and/or bending machine₁ is employed for this purpose, after the respective data regarding the paper web, the printing

press and the production type have been entered in the computer. In this case, the deformation of the paper web, which is also known by the term "fan out", is caused by moisture, by ink absorption and by mechanical stresses in the course of the passage of the paper web through several pairs of printing rollers which are arranged one after[behind] the other.

[004] Image regulation systems for counteracting the "fan out effect" are known from DE 295 01 373 U1, from DE 42 24 235 C2, from DE 43, 47 846 A1 and from[or] EP 0 938 414 B2. In these systems[, wherein] the image regulators operate mechanically or pneumatically, for example.

SUMMARY OF THE INVENTION

[005] The object of the present invention is directed to providing[based on creating] printing presses with several printing groups, which several printing groups generate at least one printed image on a material to be imprinted, and to methods for the compensation of a longitudinal elongation and/or a transverse elongation of a material to be imprinted.

[006] In accordance with the present invention, this object is attained by the provision

of the printing press with several printing groups, each of which includes a forme cylinder and an ink-transferring cylinder that transfers a portion of a common print image to a material to be printed as that material travels through the several printing groups which are arranged downstream in a production direction. The material to be imprinted has a longitudinal elongation and a transverse elongation, each expressed by an elongation factor. The locations of the printing formes on successive ones of the forme cylinders are different from those on prior ones of the forme cylinders by location factors[means of the characteristics of claims 1, 3, 5, 7, 46, 48 or 65].

[007] The advantages to be attained with the present invention lie, in particular, in that a longitudinal elongation and/or a transverse elongation of the material to be imprinted is compensated for. Factors[in that factors] affecting the longitudinal elongation and/or the[a] transverse elongation are already being taken into consideration in the course of placing the images on the printing forme. A subsequent[, so that a] positional change of one or of several of the printing formes on a forme cylinder can be preferably omitted or is only necessary to a limited extent. It[, because of which it] is thus possible to preferably omit devices for use in changing the position of one or of several printing formes on a

forme cylinder, or at least to produce such devices[them] very simply and cost-effectively.

If factors of the printing press and the material to be imprinted₁ which affect the

longitudinal elongation and/or transverse elongation of the material to be imprinted₁ are

already known, such as, for example, from experience,[and] their value can be[is]

determined and can be made available to the system for placing images on the printing

forme. It[, it] is accordingly[already] possible to match the size and the location of a print

image location on each printing forme which is participating in the printing process at the

time of producing the print image location on the printing form as needed as a function

of[to] the longitudinal elongation and/or the transverse elongation which is expected from

experience. Because these[, because of which] systematic deviations, in particular

between successive printing groups, are already compensated for, to the greatest extent,

[so that]a change of the position of the printing forme having the print image location is

preferably not required at all, or is only required for fine adjustment for updating in the

course of an ongoing printing process. Print image locations, that are already matched to

the expected longitudinal elongation and/or to the expected transverse elongation of the

material to be imprinted₁ relieve the operators of the printing press of time- consuming

checking of the correct position of the printing forme on the forme cylinder. This advantage becomes all the more important[greater] the more printing formes participate in the printing process. In a printing press which, for example, prints in four colors and which[respectively] has twelve printing formes on each forme cylinder, for example, a considerable advantage arises from already performing the matching of the print image locations to the expected longitudinal elongation and/or to the expected transverse elongation of the material to be imprinted in the course of the placement of the images. Otherwise[, since otherwise] the position of a total of forty-eight printing formes would have to be checked, and their positions[they] would have to be aligned to compensate for[for compensation of] the fan out effect on the four forme cylinders. In the case of simultaneous recto and verso printing, it is necessary, in the example mentioned, to align twice the number of printing formes, namely ninety-six, in relation to each other. An[, from which an] outlay for the checking of the position of the printing formes, as well as for their alignment, which could no longer be efficiently managed, is created for filling a printing order.

BRIEF DESCRIPTION OF THE DRAWINGS

[008] Preferred[Exemplary] embodiments of the invention are represented in the drawings and will be described in greater detail in what follows.

[009] Shown are in:

Fig. 1, a schematic side elevation representation of a printing press, suitable for multi-color printing, and having four printing units, each with two printing groups, in

Fig. 2, a schematic top plan view representation of four forme cylinders, arranged downstream of each other, and with printing formes with print image locations, in

Fig. 3, a perspective view of a printing group with print images formed[created] on a material to be imprinted, and in

Fig. 4, a holding device arranged in a channel of a forme cylinder.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[010] In a greatly simplified form, Fig. 1 schematically shows a printing press 01, preferably a printing press 01 which imprints a web 03 in several different colors, such as, for example, a printing press 01 for newspapers, and having four printing units 02 which are arranged vertically on top of each other, for example, A[, in which a] material 03 to be

imprinted, such as, for example, a web 03 of material, and in particular a paper web 03, [successively] passes vertically through the successive printing units 02. A production flow or direction P of the material 03 to be imprinted passing through the printing press 01 is assumed to substantially move from the bottom to the top, as indicated by the arrow in Fig. 1.

[011] In the configuration[example] represented schematically in Fig. 1, a respective printing group 04, including[with] a cylinder 06 for transferring ink and a forme cylinder 07 [(cylinder 07)], which rolls off on the transfer cylinder 06 which is transferring the ink image from the forme cylinder 07, is arranged on each of the two[both] sides of the paper web 03 in each printing unit 02, for accomplishing recto and verso printing. The specific representation of an associated inking system, a dampening system and further components, which are typically part of the printing group 04, for example, has been omitted here, since they are not necessary for an understanding of[explaining] the invention. The cylinders 06 transferring ink are preferably embodied as transfer cylinders 06 which are operating by [means of] the offset printing method. The[, wherein the] transfer cylinders 06 preferably each have an elastic surface. That[, wherein the] elastic

surface is constituted, for example, by [respectively]at least one printing blanket which is made of an elastomeric material and which is arranged on the shell face of the transfer cylinder 06.

[012] In the preferred embodiment[exemplary representation] of Fig. 1, the transfer cylinders 06, which are arranged on both sides of the paper web 03 in each printing unit 02, have been placed against each other in a so-called rubber-to-rubber arrangement. The two[, so that the] transfer cylinders 06, which are arranged in the same printing unit 02, alternately each function as a counter-pressure cylinder. Alternatively, two adjoining printing units 02 can be combined into a satellite printing unit. The[, wherein the] printing groups 04 of these printing units 02 are then arranged around a common counter-pressure cylinder, which is separate from the remaining cylinders 06, 07. The [, wherein the] paper web 03 is [respectively]conducted between the counter- pressure cylinder and at least one transfer cylinder 06 which is placed against the counter- pressure cylinder in such a satellite printing unit.

[013] A further alternative for the configuration[design] of the printing press 01 can provide if[for] the printing press 01 is to be configured[designed] as a job- printing press

01, and preferably as such a printing press 01 with a substantially horizontal guidance of the material 03 to be imprinted. Several[, wherein several] successive printing groups 04 are typically provided in the printing press 01 along the production flow or travel direction P of the material 03 to be imprinted, and are preferably located on both sides of the material 03, i.e. both underneath and on top of the material 03 to be imprinted. The[, wherein the] transfer cylinders 06 of two printing groups 04, which are arranged in a printing unit 02, are again placed against each other in a rubber-to-rubber arrangement. The[, wherein the] material 03 to be imprinted is conducted between the two transfer cylinders 06 which are placed against each other, so that the material 03 to be imprinted passes through the area in which the two transfer cylinders 03 [they] roll off on each other.

[014] The forme cylinders 07 which are assigned to the transfer cylinders 06[07] each have at least one printing forme 08, as seen in [(Fig. 2)], on their shell faces. In their axial direction X and/or in their circumferential direction Y, the forme cylinders 07 are each preferably covered by several printing formes 08. For example, in a newspaper printing press 01, the forme cylinders 07 are each covered, in their axial direction X, with

six printing formes 08, and are each covered, in their circumferential direction Y₁ with two printing formes 08. This results in, so that then] twelve printing formes 08 being[are] arranged on each forme cylinder 07. A developed view of such forme cylinders 07, each with twelve printing formes 08, is represented schematically in Fig. 2. The[, wherein the] directional arrows X, Y, which are part of Fig. 2₁ and which extend at right angles to each other, show the axial direction X of[in respect to] the forme cylinder 07 and the circumferential direction Y of the forme cylinder 07.

[015] To generate[For generating] a print image 11, as seen in [(Fig. 3)], on the material 03 to be imprinted, each printing forme 08 has at least one print image location 09, as shown in [(Fig. 2)]. It can [be]alternatively be provided that the printing formes 08 have several print image locations 09 in the axial direction X with[in] respect to the forme cylinder 07₁ and/or in the circumferential direction Y of the forme cylinder 07. By way of example, Fig. 3 shows the generation of six print images 11 on the material 03 to be imprinted in the axial direction X, with[in] respect to the forme cylinder 07. The production flow or direction P of the material 03 to be imprinted, as well as a production direction of rotation R of the forme cylinder 07 and of the transfer cylinder 06 working

together with the forme cylinder 07[latter], are indicated. Instead of providing, for example, six printing formes 08 in the axial direction on a forme cylinder 07, and of providing two printing formes 08 in its circumferential direction Y[for example two printing formes 08], the forme cylinders 07 can, for example, each be covered by only one printing forme 08, wherein this printing forme 08 has, for example, six print image locations 09 in the axial direction X, with[in] respect to the forme cylinder 07 and/or has, for example, two print image locations 09 in the circumferential direction Y of the forme cylinder 07[two print image locations 09, for example]. Also, every printing forme 07 can have only a single print image location 09.

[016] The printing groups 04, which are arranged one behind, or after, the other, in the production direction P, on the same side of the material 03 to be imprinted, [in its production flow P] preferably each print inks of colors that are different from each other. For example, ink dots of the colors black, cyan, magenta and yellow, which are the customary colors used in four-color printing, are printed in four successive printing groups 04. Specifically, [, namely] color dots of one of these colors are printed in each one of these four successive printing groups 04. Print image locations, which correlate with the

same resultant print image 11, are located on the forme cylinder 07 of the four successive printing groups 04. Each such print image location[, each of which] constitutes a color separation of the resultant multi-color print image to be created. Each such[, wherein each] color separation is assigned to one of the color tones to be printed. A multi-color print image 11 is formed[created] in that several color separations, such as, for example, the four color separations, which [respectively] correspond to the four respective colors, black, cyan, magenta and yellow, are printed on top of each other onto the material 03 to be imprinted. The[, wherein the] color dots of the individual color separations relating to the same resultant print image 11 are arranged either next to each other or on top of each other on the material 03 to be imprinted. The resultant[, so that the] multi- color print image 11 is formed[created] by a color mixture of the color dots resulting from the different color separations.

[017] Each print image location 09 has a width B in the axial direction X with[in] respect to the forme cylinder 07 and a print image location length L in the circumferential direction Y of the forme cylinder 07. Print image locations 09 that each constitute[constituting] a color separation, for forming[creating] a resultant common print

image 11, must be printed, or located so that they fit exactly on top of each other, by the utilization of the successive printing groups 04 which are arranged following each other in the production flow or direction P of the material 03 to be imprinted. These print image locations 09 are imprinted on the material 03 by, by means of] their respective cylinders 06 which transfer the ink from the forme cylinder 07. Adherence[Adhering] to this requirement, which is necessary for a good printing result, is made difficult since the material 03 to be imprinted customarily has a longitudinal elongation along the production flow or direction P, and/or has a transverse elongation crosswise to the production flow or direction P, which elongation occurs on the web's[its] way from one ink-transferring cylinder 06 to a successive[an] ink-transferring cylinder 06, which follows in the production flow or direction P. The longitudinal elongation and/or the transverse elongation of the material 03 to be imprinted results[result], for example, from the material 03 to be imprinted absorbing moisture that is transported to it by the dampening system of the printing press 01, and/or moisture from the ink, and/or moisture from the air surrounding the material 03 to be imprinted, and/or from a mechanical elongation of the material 03 to be imprinted when that material 03 is passing through several successively

arranged printing groups 04. Such a longitudinal elongation and/or a transverse elongation of the material 03 to be imprinted is described[known] by the term "fan out".

[018] If, in connection with a printing press 01, the distances A1, A2, A3, as shown in [(Fig. 1)], between [their] ink-transferring cylinders 06 of successive printing groups 09, which [and] are arranged one behind the other in the production flow or direction P, and a mechanical elongation of the material 03 to be imprinted, and which is possibly occurring between these successive cylinders 06, as well as the moisture-caused elongation of the material 03 to be imprinted, which moisture-caused elongation has been determined, for example, in accordance with DIN 53130, are known, it is possible[suggested] to determine what changes in the length L and/or in the width B of the print image locations 09, which create a common resultant print image 11 and which print image locations 09 are located in different printing groups 04, are to be expected. Therefore, a defined dimensional change is to be expected for each print image location 09, as a function of its position on the forme cylinder 07 and as a function of the intensity of the several above-mentioned influencing values, in comparison with another print image location 09 which is arranged on another forme cylinder 07 at the same relative position. The [wherein the]

dimensional change indicates that the length L of two print image locations 09₁ following each other in the production flow or direction P of the material 03 to be imprinted₁ differs by a factor FL. The[, and/or the] width B of two print image locations 09 following each other in the production flow or direction P of the material 03 to be imprinted₁ on successive forme cylinders 07₁ differs by a factor FB. In this case₁ the factors FL, FB can express a relative dimensional change, such as₁ for example₁ in percent, with[in] respect to an original length L or an original width B, or can express an absolute dimensional change, such as₁ for example₁ in the form of an amount of change which is based on an original length L or width B.

[019] Each print image location 09 is limited[Delimited] by its length L and width B and [, each print image location 09] defines an area₁ as seen in [(Fig. 2)], wherein the area of a print image location 09₁ which is arranged on a forme cylinder 07₁ is curved or arched₁. Its[, and its] curvature is matched to the curvature[course] of the shell face of the forme cylinder 07₁ in its circumferential direction Y. At the intersection of that area's[its] diagonal lines as [(represented in dashed lines in Fig. 2)], the area has a center point S. Alternatively to₁ or in addition to the dimensional change of a print image location 09, a

position, $[(X1, Y1)]$, of the center point S of a first[this] print image location 09 can also differ, in comparison with a position, $[(X2, Y2)]$, of a second print image location 09, which is also correlated with the resultant common print image 11, on a subsequent forme cylinder 07 which follows in the production flow P of the material 03 to be imprinted. These[, wherein these] print image locations 09 are preferably each arranged on a printing forme 08. The[, wherein the] printing formes 08, with the first and second print image locations 09, which differ in the position $[(X1, Y1)]$, $[(X2, Y2)]$ of their center points S, are arranged in the same respective position on the respective forme cylinders 07. Thus, the printing formes 08, with their respective[the] print image locations 09, remain fixed in place on their respective forme cylinders 07. Only[, while only] the position $[(X1, Y1)]$, $[(X2, Y2)]$ of at least one of the center points S of two successive print image locations 09, which are following each other in the production flow or direction P of the material 03 to be imprinted, is displaced. Only[, so that only] the positions $[(X1, Y1)]$, $[(X2, Y2)]$ of the center points S of these respective print image locations 09 are changed in relation to each other, by a distance W, as seen in [(Fig. 2)]. This is accomplished[,] without changing the position of a printing forme 08 on its respective

forme cylinder 07. The distance W is located in the same plane as is the area defined by the length L and the width B of the print image location 09, and can show the displacement of the center point S in this plane in any arbitrary direction₁ in comparison with the position [(X1, X2)] of the center point S of the related print image location 09.

[020] Since the longitudinal elongation and/or the transverse elongation of the material 03 to be imprinted can have different effects₁ depending on the position of a printing forme 08 on the forme cylinder 07, the lengths₁ L of two print image locations 09₁ which are arranged side-by-side on the same forme cylinder 07₁ in its axial direction X₁ can differ from each other by a factor FL. The₁ and/or the width B of two print image locations 09₁ which are arranged side-by-side on the same forme cylinder 07 in its axial direction X₁ can differ from each other by a factor FB. In this case, in a manner that is the same as in the previously described dimensional change, the factor FL₁ relating to the length L of the print image location 09₁ is a function of a factor DL of the web longitudinal elongation. The₁ and the factor FB₁ relating to the width B of the print image location 09₁ is a function of a factor DQ of the web transverse elongation. The₁ wherein the factor DL of the web longitudinal elongation and the factor DQ of the web transverse elongation

take into consideration, for example, the distances A1, A2, A3 between the ink-transferring cylinders 06 of the printing press 01, and which are arranged following each other in the production flow or direction P, as well as the mechanical elongation of the material 03 to be imprinted possibly occurring between these cylinders 06, as well as the moisture-caused elongation of the material 03 to be imprinted. In the course of this consideration, the length L of the print image location 09 is preferably increased by the factor DL of the web longitudinal elongation, and the width B of the print image location 09 is preferably increased by the factor DQ of the web transverse elongation. The factor DL of the web longitudinal elongation and the factor DQ of the web transverse elongation can be changeable. This[, wherein the] change can be related to further parameters, and in particular to parameters relating to operating conditions of the printing press 01 and to properties of the material 03 to be imprinted, such as, for example, the production speed of the printing press 01 or the temperature of the air surrounding the material 03 to be imprinted, and, in particular, to the moisture content of this air.

[021] Furthermore, the factor DL of the web or material longitudinal elongation and/or the factor DQ of the web or material transverse elongation can take into consideration

that, for example, the transverse elongation, with[in] respect to the print image locations 09 which are "on the outside", with[in] respect to the end[front] of the forme cylinder 07 has a greater effect than a transverse elongation with respect to[on] "inner" print image locations 09, which are arranged close to the center of the forme cylinder 07, provided a center line M, which, for example, halves the cylinder length, serves as a reference, or as a reference marker M for the transverse elongation, as seen in [(Fig. 2)]. Also, the factor FL, which differentiates the length L of two print image locations 09 following each other in the production flow or direction P of the material 03 to be imprinted, and/or the factor FB, which differentiates the width B of two print image locations 09 following each other in the production flow or direction P of the material 03 to be imprinted, can depend on the arrangement of that printing group 04 in the production flow or direction P of the material to be imprinted, in which the forme cylinder 07 with the printing form 08 having the print image location 09 whose length L and/or width B changed by the factor LB, FB is located. This is[,] because there is an effect on the value of the factors FL, FB whether the print image locations 09 of printing groups 04, which directly follow each other, or those of printing groups 04 lying farther apart, are being compared to each other.

[022] In the same way, it can be provided that the position $[(X1, Y1)]$ of the center point S of a first print image location 09 differs, in comparison with the position $[(X2, Y2)]$ of the center point S of [a]another, second print image location 09 that is arranged on the same forme cylinder 07 in the axial direction X of the latter. These, wherein these] print image locations 09 being compared have the same length L and width B. The, wherein the] print image locations 09, which are arranged side-by-side on the same forme cylinder 07, are each arranged on one printing forme 08. The, wherein the] printing formes 08, which are arranged on the same forme cylinder 07 and which have print image locations 09 whose position $[(X1, Y1)]$, $[(X2, Y2)]$ of their center points S differ, have been placed in alignment with each other in the axial direction X of the respective forme cylinder 07. Even in the case of the displacement of the position $[(X1, Y1)]$, $[(X2, Y2)]$ of the center point S of print image locations 09, which are different, but which form[create] a common print image 11, the distance W of the displacement can be a function of the factor DL of the longitudinal web or material elongation and of the factor DQ of the transverse web or material elongation, regardless of the arrangement of the print image locations 09 on the same, or on forme cylinders 07 which follow each other in

sequence in the production flow P.

[023] A channel 13, which is extending in the axial direction X underneath the shell face 12 of the forme cylinder 03, and which is provided with a preferably slit-shaped opening 14, for use in holding one or several printing formes 08 on the shell face 12 of a forme cylinder 07 is, for example, provided, [-] as can be seen in Fig. 4. Plate end [-, wherein] legs 18, 19, which are beveled or angled off the ends 16, 17 of the printing forme or formes[(s)] 08, are placed against channel walls 23, 24, which channel walls 23, 24 extend from edges 21, 22 on the shell face 12 of the opening 14 toward the interior of the channel 13. One[-, wherein one] of the plate ends 16[legs 18] has been hooked, by means of the plate end leg 18[16], which leads in the production direction R of the printing forme or formes[(s)] 08, on the wall 23, which wall 23 extends, in relation to an imaginary tangential line T resting on the opening 14, at a preferably acute opening angle α in respect to the channel 13. The[-, and the] other plate end leg 19 at the end 17 of the printing forme or formes[(s)] 08 which trails, in the production direction P of the forme cylinder 07, is held by[with] an outer end 26[28], which is oriented toward the opening 14 by the use[means] of a preferably strip-like [embodied]holding member[means] 27,

against a wall 24 which wall 24, in relation to a tangential line T resting on the opening 14, extends at a preferably approximately right- angled opening angle β in respect to the channel 13. An inner

[, wherein an] end 28 of the holding member[means] 27 that is facing away from the channel opening 14, is pivotably seated, for example in a groove 29, which is situated on, or close to, the bottom of the channel 13. An actuating element[means] 32, such as, for example, a pneumatically actuable actuating element[means] 32, and in particular a hollow body 32 which can be charged with a pressure medium, such as, for example, compressed air, and which is reversibly elastically deformable, and which is preferably a hose 32[, which] is arranged in the channel 13. Hose 32, is, [and] for example, [is] supported on a counter-thrust element 31 which is arranged in the channel 13. If the hose 32 is [, if] actuated, it pivots the at least one holding member[means] 27 against the force of at least one spring element 33, that is also preferably arranged in the channel 13. The [, wherein the] at least one spring element 33 performs a controlled lift, such as, for example, by the use[means] of a guide element 34 that is assigned to it, which is substantially directed in the circumferential direction Y of the forme cylinder 07. The

guide element 34 can be arranged on a support element 37, which itself is supported on an interior, arcuate[a] wall 36 of the channel 13. The opening 14 has a slit width V of preferably less than 5 mm at the shell face 12 of the forme cylinder 07. The[, wherein the] slit width V lies between 1 mm and 3 mm in particular. In the embodiment[example] represented in Fig. 4, the holding member[means] 27, the actuating element[means] 32 and the spring element 33 constitute essential elements of a holding device for use in holding one or several printing forms 08 on the shell face 12 of a forme cylinder 07.

[024] It is also possible, for example, to provide at least one register pin, which is [(not specifically represented)] in at least one forme cylinder 07. The[, wherein the] register pin aligns at least one printing forme[form] 08, arranged on the forme cylinder 07, in an axial direction X, with[in] regard to the forme cylinder 07. The holding device, or the register pin, is configured[designed] for working together with at least one printing forme 08 and can be shifted in the channel 13 in the axial direction X of the forme cylinder 07, such as, for example, as a function of the factor DQ of the transverse web elongation, and preferably at a ratio that is proportional to the behavior of the factor DQ of the transverse web elongation. To perform[For performing] the shifting of the printing

forme 08, which shifting is directed particularly in the axial direction X of the forme cylinder 07[in particular], preferably at least one controllable actuator, which is [(]not specifically represented)], is arranged in the forme cylinder 07, for example in its channel 13. The actuator[, wherein the actor] shifts the holding device or the register pin. The actuator can be configured[designed] as a piezo element or as a linear motor, for example. At[It can be provided that at] least one holding device or at least one register pin is preferably assigned to the printing forme 08 on each forme cylinder 07. It is advantageous if each printing forme 08 can be individually shifted in the axial direction X, with[in] respect to the forme cylinder 07.

[025] Alternatively, or in addition[additionally] to the displacement of one or of several printing formes 08 on a forme cylinder 07, it is possible to provide [that]the entire forme cylinder 07 to[can] be shiftable[shifted] in its axial direction X, so that all of the printing formes 08 arranged on it are identically shifted. When shifting one or several printing formes 08 on the forme cylinder 07, as well as when axially displacing the entire forme cylinder 07, shifting takes place transversely with[in] respect to the production flow or direction P of the material 03 to be imprinted and relative to the location of the material 03

to be imprinted, i.e. relative to a reference marker M of the material 03 to be imprinted.
The[, wherein the] reference marker M can be, for example, be the center line M of the material 03 to be imprinted, as seen in [(Fig. 2)]. However, the reference marker M can also be located at a different spot on the material 03 to be imprinted, such as, for example, at one of its lateral edges. The displacement of the printing formes 08, which is oriented transversely with[in] respect to the production flow P of the material 03 to be imprinted, can also be related to a stationary frame of the printing press 01 instead of to the material 03 to be imprinted.

[026] The forme cylinder 07 and/or the transfer cylinder 06, which transfers ink, of at least one of the two printing groups 04 that are arranged one after or behind the other in the production direction P is preferably driven by a controllable drive mechanism, which is [(not specifically represented)], such as, for example, by an electric motor, and in particular by a frequency-controlled motor. However, [it can also be provided that] each one of the forme cylinders 07 and/or the ink-transferring cylinders 06 of all printing groups 04, which are arranged one behind the other, may be [is] individually driven. When using controllable drive mechanisms, a phase relation, which is assumed with[in] respect to

each other of the forme cylinders 07 and/or of the ink-transferring cylinders 06 of at least two printing groups 04, can preferably be controlled as a function of the factor DL of the longitudinal extension. Because[By means] of the controllable phase relation of the forme cylinders 07 and/or of the ink-transferring cylinders 06, it is possible, in particular, to affect a circumferential register of the forme cylinders 07.

[027] The actuator, and/or the phase relation of the forme cylinders 07 and/or the phase relation of the ink-transferring cylinders 06, are preferably continuously controllable. The actuator, and/or the phase relation of the forme cylinders 07 and/or of the ink- transferring cylinders 06, are preferably controllable in the running production flow or direction P of the material 03 to be imprinted. In[, in] particular, the actuator, and/or the phase relation of the forme cylinders 07 and/or of the ink-transferring cylinders 06, are controllable, such as, for example, from a control console that is assigned to the printing press 01 or from another central control unit, i.e. they can be remotely controlled.

[028] It is advantageous to provide a memory unit which is connected with the control unit for at least one of the printing groups 04. The[, wherein the] memory unit contains at least one value for the factor FL of the length L of two print image locations 09 which are

located behind each other in the production flow or direction P of the material 03 to be imprinted and/or at least one value for the factor FB of the width B of two print image locations 09 which are located behind each other in the production flow or direction P of the material 03 to be imprinted. Alternatively, or additionally, the memory unit can [respectively] contain at least one value for the factor FL of the length L of two print image locations 09 which are located side-by-side on the same forme cylinder 07 and/or can contain at least one value for the factor FB of the width B of two print image locations 09 which are located side-by-side on the same forme cylinder 07. Furthermore, the memory unit can contain at least one value for the different positions [(X1, Y1)], [(X2, Y2)] of the center point S of two print image locations 09 which are located side-by-side on the same forme cylinder 07.

[029] The[It can be provided that the] control unit can track[s] the center point S of at least one print image location 09, which tracked center point follows a different print image location 09 in the production flow or direction P of the material 03 to be imprinted, with[in] respect to the center point SB of the print image 11 to be imprinted, which center point was displaced during a running printing process, such as, for example, by the

longitudinal elongation and/or by the transverse elongation of the material 03 to be imprinted, as seen in [(Fig. 3)]. In the process, the control unit controls at least the actuator and/or the phase relation of the forme cylinder 07 and/or of the ink-transferring cylinders 06, preferably as a function of the value for the factor FL and/or the factor FB and/or the positions [(X1, Y1)], [(X2, Y2)] of the center point S which is stored in the memory unit. For example, the center point S of the print image 11 to be imprinted is detected by [means of] a detector unit which is connected with the control unit, such as, for example, a device which optically detects and digitally evaluates the print image 11, and which may be, for example, a semiconductor camera with a CCD sensor. For example, the control unit can operate[s] devices, which are connected with it, with [to] the result[effect] that the center points S of the print image locations 09 which print a common print image 11 are[is] brought into agreement with the center point SB of the common print image 11 to be imprinted.

[030] Methods for compensating for the longitudinal elongation and/or for the transverse elongation, in accordance with the present invention, [here proposed] provide, [and this] preferably in advance of a shifting of at least one printing forme 08 on

a forme cylinder 07, and wherein that[the] shifting takes place in relation to a reference marker M on the material 03 to be imprinted, that the length L of at least one print image location 09 of a printing forme 08, compared with the length L of a print image location 09, which correlates with the same print image 11, of a different printing forme 08 arranged on another forme cylinder 07, is changed by the factor FL. The[, and/or the] width B of at least one print image location 09 of a printing forme 08, as compared with the width B of a print image location 09, correlating with the same print image 11 of another printing forme 08 that is arranged on another forme cylinder 07, is changed by the factor FB. Alternatively, or additionally, the position [(X1, Y1)] of a center point S of at least a first[one] print image location 09 of a printing forme 08, compared with the position [(X2, Y2)] of the center point S of a second print image location 09, correlating with the same print image 11, of another printing forme 08, that is arranged on another forme cylinder 07 at the same position of the forme cylinder 07, is changed. In the process, the length L and/or the width B and/or the position [(X1, Y1)], [(X2, Y2)] of the center point S of the print image location 09 is preferably changed by using the factor DL of the longitudinal web elongation and/or the factor DQ of the transverse web elongation.

Also, a change of the length L and/or the width B and/or the position [(X1, Y1)], [(X2, Y2)] of the center point S of the print image location 09 is preferably accomplished[performed] as a function of the position of the printing forme 08 on the forme cylinder 07, and namely of that forme cylinder 07, on which the printing forme 08₁ with the changed print image location 09₁ is arranged.

[031] A value for the factor FL, which changes the length L, is preferably determined as a function of the factor DL of the longitudinal web elongation. A[, and a] value for the factor FB, which changes the width B, is preferably determined as a function of the factor DQ of the transverse web elongation. The value for the factor FL, which changes the length L, and/or the value for the factor FB, which changes the width B, and/or which changes the coordinates for a new position of the [(X1, Y1)], [(X2, Y2)] of the center point S of the print image location 09 on the printing forme 08 on one of the forme cylinders 07 can also be determined as a function of the print image location 09 of a different printing forme 08, that is arranged in the same position on the forme cylinder 07₁ on a different forme cylinder 07.

[032] A change of the position L and/or of the width B of a print image location 09, or a

change of the position $[(X1, Y1)], [(X2, Y2)]$ of its center point S_1 for compensating for a portion of the longitudinal elongation and/or of the transverse elongation, which is known at the time the image was applied to the printing forme 08_1 is preferably performed wherein[in that] a printing forme 08_1 with a print image location 09 which was changed in its above-mentioned parameters₁ is arranged on a forme cylinder 07 in the same position of a forme cylinder 07 having a printing forme 08 with a print image location 09 which is to be changed. In this way₁ at least a part of the compensation of the "fan out effect" takes place in connection with the provision of an image on the printing forme 08, i.e. in the course of determining[creating] the print image location 09. A print image location 09 which, in comparison with the print image location 09 of another printing forme 08, has already been changed₁ with respect[in regard] to its dimensions, and/or with respect to the position $[(X1, Y1)], [(X2, Y2)]$ of its center point S_1 is arranged at the position on a forme cylinder 07 that is intended for it. In this case₁ the change is performed to the extent that the change of the dimension and/or of the position $[(X1, Y1)], [(X2, Y2)]$ of its center point S of the print image location 09 is to be expected, such as, for example, as a function of the factor DL of the longitudinal web elongation, and/or the factor DQ of

the transverse web elongation of the material web 03 to be imprinted, and/or as a function of the position of the print image location 09 on one of the forme cylinders 07, as well as possibly as a function also of further previously known or determinable parameters. Thus, the change relates to a change of the dimension and/or of the position of the print image location 09 on a printing forme 08, so that systematic deviations, which are to be expected between at least two print image locations 09, are compensated for. Because of this, a change of the position of the printing forme 08 on the forme cylinder 09 is often[is] no longer required, or is only required for fine adjustment or for updating in the course of an[the] ongoing printing process.

[033] To begin with, known or determinable parameters, for taking into consideration the required change of the dimension and/or position of the print image location 09 on a printing forme 08, such as, for example, the factor DL of the longitudinal web elongation, and/or the factor DQ of the transverse web elongation of the material 03 to be imprinted, are supplied to an image application system. That[wherein the] image application system applies the print image location 09, such as, for example, by the use[means] of a laser, to the printing forme 08, and is preferably controlled by [means of] a computer and on the

basis of a digital data set. Therefore, the image application system forms[creates] the print image location 09 on a printing forme 08 in accordance with [the]predetermined conditions and, in this way, compensates for the results of the "fan out effect" which are to be expected. In the image application process, the image application system applies the images to the printing forme 08, in particular as a function of the color tone of the cylinder 06 which is transferring the ink, and/or as a function of the arrangement of the printing group 04, with [in] respect to the forme cylinder 07 that is carrying the printing forme 08 in the production flow P of the material 03 to be imprinted, and/or as a function of the position of the printing forme 08 which is arranged on the forme cylinder 07. Thus, in the course of forming[creating] a print image location 09, the image application system takes into consideration its position on the forme cylinder 08. This[, wherein this] position is customarily determined by [means of]an occupation plan that is conceived[created] in a pre-printing stage. Based on the position of the printing forme 08, in accordance with the occupation plan, on one of the forme cylinders 07, the image application system then matches at least some print image locations 09, and preferably matches each print image location 09 in a further printing group 04 that is following a first printing group 04, in its

length L, and/or width B, and/or in the position of its center point S, as a function of the above-mentioned influencing values₁ which were taken into consideration during the formation[creation] of the same print image 11. This is done[.] in order to counteract systematic deviations, which are to be expected in the course of the ongoing printing process₁ and to compensate for these deviations, [them] as much as possible₁ by a suitable [design and/or]arrangement, or[i.e.] positioning[.], of the print image location 09.

[034] In a further development of the [proposed]method in accordance with the present invention, a desired value of the factor FL for changing the length L, and/or a desired value of the factor FB for changing the width B, and/or a desired value of the position of the center point S of a print image location 09 of a printing forme 08 to be changed, are continuously determined. Parameters [in that parameters], which are relevant to the above-mentioned changes, are detected and their values are matched₁ in the course of the ongoing printing process. It is then possible to arrange a printing forme 08₁ containing the changed print image location 09₁ on at least one forme cylinder 07₁ if an actual value of the factor FL for changing the length L, and/or a actual value of the factor FB for changing the width B, and/or an actual value of the position [(X1, Y1)],

[(X2, Y2)] of the center point S of the print image location 09 of a printing forme 08 exceeds a permissible deviation from the determined desired values. However, to attain this end, the preparation[creation] of a printing forme 08 with a changed print image location 09, and its exchange on the forme cylinder 07 which is involved is required. This[, which] can require[mean] an interruption of the printing process.

[035] The[For example, the] desired values may be[are] determined for each color tone which is transferred by an ink-transferring cylinder 06. Alternatively[Or], the desired values may be[are] determined for each forme cylinder 07 of the printing groups 04 that are following each other in the production flow or direction P of the material 03 to be imprinted, and/or for each position of a printing forme 08 which is arranged on one of the forme cylinders 07. The determined desired values are preferably stored in a memory and are made available to the image application system as required.

[036] It is furthermore possible, in accordance with the present invention, to counteract at least a part of the transverse elongation of the material 03 to be imprinted by[means of] employing an image regulator 38, as depicted schematically in [(Fig. 1)], wherein, prior to its entry into a subsequent or following printing group 04, the material 03

to be imprinted is deformed, preferable in a wave shape, by the image regulator 38 transversely to its production direction R. In and in] this way, the material 03 is reduced, in its width B03, in a manner which counteracts the transverse elongation, as seen in [(Fig. 3)]. Preferably, the intensity or the extent of the width reduction takes place at a reverse ratio with[in] respect to the factor DQ of the transverse web elongation, and can preferably also be changed in the course of the ongoing printing process. The deformation of the material 03 to be imprinted can take place, for example, mechanically by the use[means] of rollers which are preferably placed against [it on] both sides of the material 03 to be deformed. To prevent the occurrence of wherein, for preventing negative effects on the quality, these rollers preferably act outside of the print image 11 on the material 03 to be imprinted and are preferably individually rotatorily driven. Another embodiment of the image regulator 38 provides at least one air nozzle that is directed onto the surface of the material 03 to be imprinted. This at least one air nozzle, [which] for example, permits compressed air to flow against the material 03 to be imprinted. In and in] this way the air nozzle deforms the material 03 to be imprinted in a contactless manner. Preferably, several such air nozzles are provided in connection with

this pneumatic image regulator 38, which air nozzles are spaced apart from each other . Preferably[, preferably] at least three air nozzles are provided, wherein the air flow of an[the] air nozzle, which is arranged between two other air nozzles is preferably directed counter to the air flow direction of its adjoining air nozzles. The result is[, so] that the material 03 to be imprinted, which is charged with the air flow, is deformed in a wave shape. With use of the mechanical, as well as with use of the pneumatic image regulator 38, the deformation of the material 03 to be imprinted can [be]preferably be continuously controlled within defined limits by a control unit which controls the image regulator 38. In [, in] particular, this deformation[it] can be [remotely]controlled remotely from a control console which is part of the printing press 01. The control unit can change the center point SB of the print image 11 by actuating the image regulator 38.

[037] While preferred embodiments of a printing machine with a device and a method for compensation of a longitudinal elongation and a transverse elongation of a printed web printed in differing printing couples, in accordance with the present invention, have been set forth fully and completely hereinabove, it will be apparent to one of skill in the art that various changes in, for example, the sizes of the cylinders, the specific inking and

[WO 2005/072966]

[PCT/EP2005/050261]

dampening units, and the like could be made without departing from the true spirit and scope of the present invention which is accordingly to be limited only by the appended claims.

WHAT IS CLAIMED IS:

[List of Reference Symbols

- 01 Printing press, newspaper printing press, job-printing press
- 02 Printing unit
- 03 Material to be imprinted, web of material, paper web
- 04 Printing group
- 05 -
- 06 Ink-transferring cylinder, transfer cylinder
- 07 Cylinder, forme cylinder
- 08 Printing forme
- 09 Print image location
- 10 -
- 11 Print image
- 12 Shell face
- 13 Channel
- 14 Opening
- 15 -
- 16 End
- 17 End
- 18 Leg
- 19 Leg
- 20 -
- 21 Edge
- 22 Edge
- 23 Wall
- 24 Wall
- 25 -]

- [26] End
- 27 Holding means
- 28 End
- 29 Groove
- 30 -
- 31 Counter-thrust element
- 32 Actuating means, hollow body, hose
- 33 Spring element
- 34 Guide element
- 35 -
- 36 Wall
- 37 Support element
- 38 Image regulator

- B Width (09)
- L Length (09)
- M Center line, reference marker
- P Production flow
- R Production direction
- S Center point (09)
- T Tangential line
- V Slit width
- W Distance
- X Axial direction, directional arrow
- Y Circumferential direction, directional arrow

- SB Center (11)

- A1 Distance
- A2 Distance
- A3 Distance]

[WO 2005/072966]

[PCT/EP2005/050261]

[B03 Width (03)

X1, Y1 Position

X2, Y2 Position

α Opening angle

β Opening angle]